WEVER & DUCRÉ LIGHTING

THEMIS 2.7

3238A1W2

PROJECT

TYPE

NOTES

QUANTITY

DATE





Rectangular wall recessed luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; recessed depth 50mm; suitable for ceiling thickness of 2-18 mm; PCB; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 80; degree of protection IP20; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall
Recessed
White Matt
RAL 9010 [a]
IP20
Interior
310 lm / 700mA
235 lm / 500mA

LED MODULE

2700 K
CRI ≥ 80
≤ 3 SDCM (initial MacAdam)
235 lm / 500mA
81 lm/W [b]
2.9 W [b]

OPTICAL

Asymetric
CIE flux code: 31 60 81 73 100

ELECTRICAL

excl. driver
6 V
Class III

PHYSICAL

length 80 mm
width 47 mm
height 270 mm
0.31 kg

CUTOUT

length 70 mm
width 258 mm
min. ceiling thickness 2 mm
max. ceiling thickness 18 mm
recessed depth 50 mm

[a] Colour may deviate slightly due to production conditions
[b] Without electrical and optical losses

LIGHT DISTRIBUTION





ELECTRICAL ACCESSORIES

DRIVER

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
6W | 500mA | 3-12V | 100-240VAC		3-12V	68·35·21	90214201
6W | 700mA | 3-8.4V | 90-295VAC		3-8,4V	68·35·21	90215203

MOUNTING ACCESSORIES

PLASTERKIT

TYPE	COLOUR	VOLTAGE	L·H (MM)	ITEM NUMBER
THEMIS 2.7			180·370	90017112

RECESSED HOUSING

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
THEMIS 2.7			180·83·370	90012033

['3238A1W2'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com