




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Rectangular wall recessed luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; recessed depth 55 mm; suitable for ceiling thickness of 2-25 mm; PCB 3-step binning; light colour 3000 K;  $\leq 3$  SDCM (initial MacAdam); CRI  $\geq 80$ ; degree of protection IP20; Class 3; driver not included; light source not replaceable;



**LUMINAIRE**

Wall \_\_\_\_\_  
 Recessed \_\_\_\_\_  
 White Matt \_\_\_\_\_  
 RAL 9010 <sup>a</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 275 / 365 lm \_\_\_\_\_

**LED Module**

3000 K \_\_\_\_\_  
 CRI  $\geq 80$  \_\_\_\_\_  
 L80 / 100000 h \_\_\_\_\_  
 $\leq 3$  SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

Asymmetric \_\_\_\_\_  
 CIE flux code: 31 60 81 73 100 \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_  
 6 V \_\_\_\_\_  
 Class III \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**

length 78 mm \_\_\_\_\_  
 width 51 mm \_\_\_\_\_  
 height 168 mm \_\_\_\_\_  
 0.24 kg \_\_\_\_\_

**Cutout**



length 86 mm \_\_\_\_\_  
 width 170 mm \_\_\_\_\_  
 min. ceiling thickness 2 mm \_\_\_\_\_  
 max. ceiling thickness 25 mm \_\_\_\_\_  
 recessed depth 55 mm \_\_\_\_\_

**datasheet.quicksum.material**

Aluminium \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**



[3207A1W4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.99	0.97	0.95	0.94	0.92
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

**ELECTRICAL ACCESSORIES**

**Driver**

Type	Colour	Voltage	L·W·H (MM)	Item number
6W   500mA   3-12V		3-12V	68-35-21	90214201
6W   700mA   3-8.4V		3-8,4V	68-35-21	90215203