




PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Disc shaped wall surface luminaire No matching RAL; PCB 3-step binning; phase-cut dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 2; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

LUMINAIRE

Wall _____

Surface _____

Champagne Brushed _____

No matching RAL _____

IP20 _____

Interior _____

415 lm _____

LED Module

2700 K _____

CRI ≥ 90 _____

L80 / 70000 h _____

≤ 3 SDCM (initial MacAdam) _____

Optical

Indirect _____

CIE flux code: 0 2 28 22 100 _____

Electrical

phase-cut dim _____

220 - 240 V _____

system 8.5 W _____

Class II _____

Standard _____

Physical

diameter 260 mm _____



height 38 mm _____

1.07 kg _____

datasheet.quicksum.material

Aluminium _____

LIGHT DISTRIBUTION





Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.92	0.89	0.86
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.