



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Hexagonal ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class I; UGR ≤ 10 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 1500$ cd/m²; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling _____

Surface _____

Black Matt _____

RAL 9011 ^a _____

IP20 _____

Interior _____

585 lm _____

LED Module

2700 K _____

CRI ≥ 90 _____

L70 / 50000h _____

≤ 3 SDCM (initial MacAdam) _____

730 lm _____

91 lm/W ^b _____

Optical

Medium (standard) _____

beam angle 21° _____

CIE flux code: 93 99 100 100 _____

100 _____

Electrical

phase-cut dim _____

220 - 240 V _____

system 8.1 W _____

Class I _____

Standard _____

Physical

length 220 mm _____

width 127 mm _____

height 100 mm _____


1.13 kg _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses

LIGHT DISTRIBUTION





Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0	0	0	0	0
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL ACCESSORIES

Single Inner Cover

Type	Colour	Voltage	L·W·H (MM)	Item number
HEXO max. 10W	Black		77.4-67-54	911031B1
HEXO max. 10W	Gold		77.4-67-54	911031G1
HEXO max. 10W	White		77.4-67-54	911031W1