



WEVER & DUCRÉ
LIGHTING

BOX 2.0 LED

186258L3 911011M1

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Surface

Aluminium Brushed

Inset: Champagne

IP20

Interior

Output: 1340 lm

CIE flux code: 96 99 100 100 100

LED

2700 K

CRI ≥ 90

3 SDCM

OPTICAL

Medium , Beam angle 21°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 16.0 W

Class 1

PHYSICAL

Length 188 mm


Width 100 mm

Height 100 mm

1.08 kg



Rectangular ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; PC1; UGR ≤ 13 ; inclusive single inner cover in Champagne; light source replaceable by an authorized professional;





BOX
2.0 LED

186258L3 911011M1

COMPONENTS

Single Inner Cover

TYPE	L · W · H (MM)	ORDERCODE
BOX max. 10W	62 · 62 · 49	9 1 1 0 1 1 M 1