



PROJECT

TYPE


NOTES

QUANTITY

DATE



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Copper; wet painted; brushed; No matching RAL; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class I; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 1500 \text{ cd/m}^2$; optional single inner reflector and single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Surface
Copper
No matching RAL
IP20
Interior
585 lm

LED Module

2700 K
CRI ≥ 90
L70 / 50000h
 ≤ 3 SDCM (initial MacAdam)
730 lm
91 lm/W^a

Optical

Medium (standard)
beam angle 21°
CIE flux code: 93 99 100 100 100

Electrical

DALI
220 - 240 V
system 8.1 W
Class I
Standard

Physical


length 100 mm
width 100 mm
height 100 mm
0.74 kg

datasheet.quicksum.material

Aluminium

^a Without electrical and optical losses

LIGHT DISTRIBUTION





Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0	0	0	0	0
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL ACCESSORIES

Single Inner Cover

Type	Colour	Voltage	L·W·H (MM)	Item number
BOX max. 10W	Black		62-62-49	911011B1
BOX max. 10W	Gold		62-62-49	911011G1
BOX max. 10W	Champagne		62-62-49	911011M1
BOX max. 10W	White		62-62-49	911011W1

Single Inner Reflector

Type	Colour	Voltage	L·W·H (MM)	Item number
BOX max. 10W	Black		93.5-93.5-50.5	911211B1
BOX max. 10W	Gold		93.5-93.5-50.5	911211G1
BOX max. 10W	Champagne		93.5-93.5-50.5	911211M1
BOX max. 10W	White		93.5-93.5-50.5	911211W1