



WEVER & DUCRÉ
LIGHTING

BOX 1.0 LED

186159L3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Surface

Aluminium Brushed

IP20

Interior

Output: 670 lm

CIE flux code: 95 99 100 100 100

LED

2700 K

CRI ≥ 90

3 SDCM

OPTICAL

Medium , Beam angle 21°

ELECTRICAL

DALI

220 - 240 V

Total connected power 8.0 W

Class 1

PHYSICAL

Length 100 mm


Width 100 mm

Height 100 mm

0.74 kg



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; PC1; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; optional single inner reflector and single inner cover available; light source replaceable by an authorized professional;





WEVER & DUCRÉ
LIGHTING

BOX 1.0 LED

186159L3

INNER REFLECTOR

Single Inner Reflector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
BOX max. 10W	Black	93.5-93.5-50.5	9 1 1 2 1 1 B 1
BOX max. 10W	Gold	93.5-93.5-50.5	9 1 1 2 1 1 G 1
BOX max. 10W	Champagne	93.5-93.5-50.5	9 1 1 2 1 1 M 1
BOX max. 10W	White	93.5-93.5-50.5	9 1 1 2 1 1 W 1

INNER COVER

Single Inner Cover

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
BOX max. 10W	Black	62-62-49	9 1 1 0 1 1 B 1
BOX max. 10W	Gold	62-62-49	9 1 1 0 1 1 G 1
BOX max. 10W	Champagne	62-62-49	9 1 1 0 1 1 M 1
BOX max. 10W	White	62-62-49	9 1 1 0 1 1 W 1