



WEVER & DUCRÉ
LIGHTING

BOX 1.0 LED

186158L5 911211G1

GENERAL

Ceiling , Surface

Aluminium Brushed

Inset: Gold

IP20

Interior

Output: 700 lm

CIE flux code: 96 99 100 100 100

LED

3000 K

CRI \geq 90

3 SDCM

OPTICAL

Medium , Beam angle 21°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 8.0 W

Class 1

PHYSICAL

Length 100 mm

Width 100 mm

Height 100 mm

0.74 kg

Project

Type


Notes

Quantity

Date



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; 220 - 240 V; degree of protection IP20; PC1; UGR \leq 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° \leq 3000 cd/m²; inclusive single inner reflector in Gold; light source replaceable by an authorized professional;





WEVER & DUCRÉ
LIGHTING

BOX 1.0 LED

186158L5 911211G1

COMPONENTS

Single Inner Reflector

TYPE	L · W · H (MM)	ORDERCODE
BOX max. 10W	93.5-93.5-50.5	9 1 1 2 1 1 G 1