



WEVER & DUCRÉ
LIGHTING

BOX 1.0 LED

186158L3 911211B1

GENERAL

Ceiling , Surface

Aluminium Brushed

Inset: Black

IP20

Interior

Output: 670 lm

CIE flux code: 99 100 100 100 100

LED

2700 K

CRI ≥ 90

3 SDCM

OPTICAL

Medium , Beam angle 21°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 8.0 W

Class 1

PHYSICAL

Length 100 mm

Width 100 mm

Height 100 mm

0.74 kg

Project

Type


Notes

Quantity

Date



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; PC1; UGR ≤ 10 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; inclusive single inner reflector in Black; light source replaceable by an authorized professional;





WEVER & DUCRÉ
LIGHTING

BOX 1.0 LED

186158L3 911211B1

COMPONENTS

Single Inner Reflector

| TYPE | L · W · H (MM) | ORDERCODE |
|----------------|--------------------|-----------------|
| BOX max. 10W | 93.5 · 93.5 · 50.5 | 9 1 1 2 1 1 B 1 |