



WEVER & DUCRÉ  
LIGHTING

# BOX 1.0 LED

186158L3

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling , Surface

Aluminium Brushed

IP20

Interior

Output: 670 lm

CIE flux code: 95 99 100 100 100

## LED

2700 K

CRI  $\geq 90$

3 SDCM

## OPTICAL

Medium , Beam angle 21°

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 8.0 W

Class I

## PHYSICAL

Length 100 mm


Width 100 mm

Height 100 mm

0.74 kg



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP20; PC1; UGR  $\leq 13$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65°  $\leq 1500$  cd/m<sup>2</sup>; optional single inner reflector and single inner cover available; light source replaceable by an authorized professional;



BOX

1.0 LED

186158L3

INNER REFLECTOR

Single Inner Reflector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
BOX   max. 10W	Black	93.5-93.5-50.5	9 1 1 2 1 1 B 1
BOX   max. 10W	Gold	93.5-93.5-50.5	9 1 1 2 1 1 G 1
BOX   max. 10W	Champagne	93.5-93.5-50.5	9 1 1 2 1 1 M 1
BOX   max. 10W	White	93.5-93.5-50.5	9 1 1 2 1 1 W 1

INNER COVER

Single Inner Cover

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
BOX   max. 10W	Black	62-62-49	9 1 1 0 1 1 B 1
BOX   max. 10W	Gold	62-62-49	9 1 1 0 1 1 G 1
BOX   max. 10W	Champagne	62-62-49	9 1 1 0 1 1 M 1
BOX   max. 10W	White	62-62-49	9 1 1 0 1 1 W 1