



WEVER & DUCRÉ  
LIGHTING

# BOX 1.0 LED

186158L3 911011M1

## GENERAL

Ceiling , Surface

Aluminium Brushed

Inset: Champagne

IP20

Interior

Output: 670 lm

CIE flux code: 96 99 100 100 100

## LED

2700 K

CRI  $\geq 90$

3 SDCM

## OPTICAL

Medium , Beam angle 21°

## ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 8.0 W

Class 1

## PHYSICAL

Length 100 mm

Width 100 mm

Height 100 mm

0.74 kg


Project

Type


Notes

Quantity

Date



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Aluminium Brushed; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP20; PC1; UGR  $\leq 16$ ; inclusive single inner cover in Champagne; light source replaceable by an authorized professional;





WEVER & DUCRÉ  
LIGHTING

# BOX 1.0 LED

186158L3 911011M1

## COMPONENTS

### Single Inner Cover

TYPE	L · W · H (MM)	ORDERCODE
BOX   max. 10W	62 · 62 · 49	9 1 1 0 1 1 M 1