




## PROJECT

## TYPE


## NOTES

## QUANTITY

## DATE



Bedside luminaire made from die-cast aluminium with rectangular base; inclusive on/off switch in white; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K;  $\leq 2$  SDCM (initial MacAdam); CRI  $\geq 90$ ; beam angle 30°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class I; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



## LUMINAIRE

Wall  
Surface  
tilt max 90 °  
rotation 350 °  
White Matt  
RAL 9010 <sup>a</sup>  
IP20  
Interior  
345 lm

## LED Module

3000 K  
CRI  $\geq 90$   
L80 / 50000h  
 $\leq 2$  SDCM (initial MacAdam)  
344 lm  
70 lm/W <sup>b</sup>

## Optical

Medium (standard)  
beam angle 30°  
CIE flux code: 97 100 100 100  
100


## Electrical

incl. driver  
220 - 240 V  
system 4.9 W  
Class I

## Physical

diameter 26 mm  
height 117 mm  
0.24 kg

## LIGHT DISTRIBUTION



<sup>a</sup> Colour may deviate slightly due to production conditions  
<sup>b</sup> Without electrical and optical losses

**CONE DIAGRAM**

medium (standard) 30°

h (m)	E0° (lx)	ø (m)
1	1000	0.54
2	250	1.09
3	110	1.63
4	60	2.18
5	40	2.72