




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Bedside luminaire made from die-cast aluminium with rectangular base; inclusive on/off switch in white; surface White Matt; powder coated, matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K;  $\leq 2$  SDCM (initial MacAdam); CRI  $\geq 90$ ; beam angle 30°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



**LUMINAIRE**

Wall \_\_\_\_\_  
 Surface \_\_\_\_\_  
 tilt max 90° \_\_\_\_\_  
 rotation 350° \_\_\_\_\_  
 White Matt \_\_\_\_\_  
 RAL 9010<sup>a</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 330 lm \_\_\_\_\_

**LED Module**

2700 K \_\_\_\_\_  
 CRI  $\geq 90$  \_\_\_\_\_  
 L80 / 50000h \_\_\_\_\_  
 $\leq 2$  SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

Medium (standard) \_\_\_\_\_  
 beam angle 30° \_\_\_\_\_  
 CIE flux code: 97 100 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**Electrical**

incl. driver | incl. switch on/off \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 4.9 W \_\_\_\_\_  
 Class I \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**


diameter 26 mm \_\_\_\_\_  
 height 117 mm \_\_\_\_\_  
 0.24 kg \_\_\_\_\_

**datasheet.quicksum.material**

Aluminium \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**



[177353W3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



## CONE DIAGRAM

medium (standard) 30°

h (m)	E0° (lx)	ø (m)
1	954	0.54
2	238	1.09
3	106	1.63
4	60	2.18
5	38	2.72