




PROJECT

TYPE


NOTES

QUANTITY

DATE



Bedside luminaire made from die-cast aluminium with rectangular base; inclusive on/off switch in white; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 30°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class I; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



LUMINAIRE

Wall
Surface
tilt max 90 °
rotation 350 °
White Matt
RAL 9010 ^a
IP20
Interior
330 lm

LED Module

2700 K
CRI ≥ 90
L80 / 50000h
 ≤ 2 SDCM (initial MacAdam)
328 lm
67 lm/W ^b

Optical

Medium (standard)
beam angle 30°
CIE flux code: 97 100 100 100
100


Electrical

incl. driver
220 - 240 V
system 4.9 W
Class I

Physical

diameter 26 mm
height 117 mm
0.24 kg

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses



CONE DIAGRAM

medium (standard) 30°

h (m)	E0° (lx)	ø (m)
1	954	0.54
2	238	1.09
3	106	1.63
4	60	2.18
5	38	2.72