




PROJECT

TYPE


NOTES

QUANTITY

DATE



Bedside luminaire made from die-cast aluminium with rectangular base; inclusive on/off switch in black; surface Black Matt; powder coated, matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 30°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class I; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



LUMINAIRE

Wall _____
 Surface _____
 tilt max 90 ° _____
 rotation 350 ° _____
 Black Matt _____
 RAL 9011 ^a _____
 IP20 _____
 Interior _____
 345 lm _____


LED Module

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 ≤ 2 SDCM (initial MacAdam) _____

Optical

Medium (standard) _____
 beam angle 30° _____
 CIE flux code: 97 100 100 100 _____
 100 _____

LIGHT DISTRIBUTION



Electrical

incl. driver | incl. switch on/off _____
 220 - 240 V _____
 system 4.9 W _____
 Class I _____
 Standard _____

Physical

diameter 26 mm _____
 height 117 mm _____
 0.24 kg _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions



CONE DIAGRAM

medium (standard) 30°

h (m)	E0° (lx)	ø (m)
1	1000	0.54
2	250	1.09
3	110	1.63
4	60	2.18
5	40	2.72