




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_




Ceiling surface luminaire with 2 spotlights; made from die-cast aluminium; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K;  $\leq 2$  SDCM (initial MacAdam); CRI  $\geq 90$ ; beam angle 30°; 350° rotatable and 90° tiltable; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



**LUMINAIRE**

- \_\_\_\_\_ Ceiling
- \_\_\_\_\_ Surface
- \_\_\_\_\_ tilt max 90 °
- \_\_\_\_\_ rotation 350 °
- \_\_\_\_\_ Black Matt + Aluminium
- \_\_\_\_\_ Brushed
- \_\_\_\_\_ RAL 9011 <sup>a</sup>
- \_\_\_\_\_ IP20
- \_\_\_\_\_ Interior
- \_\_\_\_\_ 1100 lm

**LIGHT DISTRIBUTION**



**LED Module**

- \_\_\_\_\_ 3000 K
- \_\_\_\_\_ CRI  $\geq 90$
- \_\_\_\_\_ L80 / 50000h
- \_\_\_\_\_  $\leq 2$  SDCM (initial MacAdam)
- \_\_\_\_\_ 550 lm
- \_\_\_\_\_ 63 lm/W <sup>b</sup>

**Optical**

- \_\_\_\_\_ Medium (standard)
- \_\_\_\_\_ beam angle 30°
- \_\_\_\_\_ CIE flux code: 97 100 100 100
- \_\_\_\_\_ 100

**Electrical**

- \_\_\_\_\_ phase-cut dim
- \_\_\_\_\_ 220 - 240 V
- \_\_\_\_\_ system 17.5 W
- \_\_\_\_\_ Class I
- \_\_\_\_\_ Standard

**Physical**

- \_\_\_\_\_ length 200 mm
- \_\_\_\_\_ width 26 mm
- \_\_\_\_\_ height 117 mm
- \_\_\_\_\_ 0.42 kg

**datasheet.quicksum.material**

Aluminium

<sup>a</sup> Colour may deviate slightly due to production conditions  
<sup>b</sup> Without electrical and optical losses



## CONE DIAGRAM

medium (standard) 31°

h (m)	EO° (lx)	ø (m)
1	1530	0.56
2	380	1.12
3	170	1.67
4	100	2.23
5	60	2.79