



**PROJECT**

---

**TYPE**

---

**NOTES**

---

**QUANTITY**


---

**DATE**

---



Suspended luminaire for 48V tracks made from aluminium; track adapter with height adjustable cable system; surface Aluminium Brushed; RAL 9006; polycarbonate track adapter and cable in Signal Black; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 2700 K;  $\leq 2$  SDCM (initial MacAdam); CRI  $\geq 90$ ; 48 V; beam angle 33°; degree of protection IP20; Class 3; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



**LUMINAIRE**

Ceiling  
 Track Suspended  
 Aluminium Brushed  
 RAL 9006 <sup>a</sup>  
 IP20  
 Interior  
 435 lm

**LED Module**

2700 K  
 CRI  $\geq 90$   
 L80 / 90000 h  
 $\leq 2$  SDCM (initial MacAdam)

**Optical**

Medium  
 beam angle 33°  
 CIE flux code: 91 97 99 100 100

**Electrical**

DALI-2  
 48 V  
 Class III  
 Standard

**Physical**


diameter 26 mm  
 height 300 mm  
 0.18 kg  
 cable length 950-1200 mm  
 adapter 175 mm  
 incl. STREX 48V track adapter

**datasheet.quicksum.material**

Aluminium

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**





## CONE DIAGRAM

medium 34°

h (m)	E0° (lx)	ø (m)
1	948	0.62
2	237	1.23
3	105	1.85
4	59	2.47
5	38	3.08

## Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.93	0.9	0.88
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF<sup>a</sup> Luminaire Maintenance Factor

RSMF<sup>a</sup> Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## TRACK ACCESSORIES

### Blank Cover 2m

Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system	Black		2000-18-3	911002B0
STREX system	White		2000-18-3	911002W0

### Connector

Type	Colour	Voltage	L·H (MM)	Item number
STREX system	Black		105-18	904431B0
STREX system	White		105-18	904431W0

### End Cap

Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system   recessed	Black		37-10-27	904121B0
STREX system   recessed	White		37-10-27	904121W0
STREX system   surface/suspended	Black		26-2.5-29	904221B0
STREX system   surface/suspended	Champagne		26-2.5-29	904221M0
STREX system   surface/suspended	Bronze		26-2.5-29	904221Q0
STREX system   surface/suspended	White		26-2.5-29	904221W0

### L-Connector

Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system   recessed	Black		105-105-19	904132B0
STREX system   recessed	White		105-105-19	904132W0
STREX system   surface/suspended	Black		105-105-19	904232B0
STREX system   surface/suspended	Champagne + Black		105-105-19	904232MB0
STREX system   surface/suspended	Bronze + Black		105-105-19	904232QB0
STREX system   surface/suspended	White		105-105-19	904232W0

[179265L3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.


**L-Connector non-electrical**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   recessed	Black		105-105-19	904133B0
STREX system   recessed	White		105-105-19	904133W0
STREX system   surface	Black		105-105-19	904233B0
STREX system   surface	Champagne + Black		105-105-19	904233MB0
STREX system   surface	Bronze + Black		105-105-19	904233QB0
STREX system   surface	White		105-105-19	904233W0

**Mounting Bracket**

Type	Colour	Voltage	Item number
STREX system   recessed			90414110

**Power Feed**

Type	Colour	Voltage	L-H (MM)	Item number
STREX system	Black		112-18	904451B0
STREX system	White		112-18	904451W0

**Suspension Set**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   1.5m   suspended	Black		80-23-1500	904341B0
STREX system   1.5m   suspended	Stainless Steel		80-23-1500	90434110
STREX system   3.0m   suspended	Black		80-23-3000	904342B0
STREX system   3.0m   suspended	Stainless Steel		80-23-3000	90434210

**T-Connector**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   surface	Black		275-146-18	904234B0
STREX system   surface	White		275-146-18	904234W0

**Wireless Casambi Control**

Type	Colour	Voltage	L-H (MM)	Item number
STREX system	Black		143-58	904491B0
STREX system	White		143-58	904491W0

**X-Connector**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   surface	White		275-275-18	904235B0
STREX system   surface	Black		275-275-18	904235W0

**ELECTRICAL ACCESSORIES**
**Ceiling Driver 100W**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   suspended	Black		439-26-44	904361B0
STREX system   suspended	White		439-26-44	904361W0

**Ceiling Driver 150W**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   suspended	Black		439-26-44	904371B0
STREX system   suspended	White		439-26-44	904371W0



<b>Driver</b>				
Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system   100W		48V	350-30-18	90218901
STREX system   150W		48V	350-30-18	90218902

<b>In Line Driver 100W</b>				
Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system   surface	Black		439-26-44	904262B0
STREX system   surface	White		439-26-44	904262W0
STREX system   suspended	Black		439-26-44	904362B0
STREX system   suspended	White		439-26-44	904362W0

<b>In Line Driver 150W</b>				
Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system   surface	Black		439-26-44	904272B0
STREX system   surface	White		439-26-44	904272W0
STREX system   suspended	Black		439-26-44	904372B0
STREX system   suspended	White		439-26-44	904372W0

<b>In Track Driver 100W</b>				
Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system   surface	Black		468-26-29	904263B0
STREX system   surface	Champagne + Black		468-26-29	904263MB0
STREX system   surface	Bronze + Black		468-26-29	904263QB0
STREX system   surface	White		468-26-29	904263W0
STREX system   surface	Black		438-16-18	904264B0
STREX system   surface	White		438-16-18	904264W0
STREX system   suspended	Black		3000	904363B0
STREX system   suspended	Champagne + Black		3000	904363MB0
STREX system   suspended	Bronze + Black		3000	904363QB0
STREX system   suspended	White		3000	904363W0

<b>In Track Driver 250W</b>				
Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system   surface	Black		438-26-29	904283B0
STREX system   surface	Champagne + Black		438-26-29	904283MB0
STREX system   surface	Bronze + Black		438-26-29	904283QB0
STREX system   surface	White		438-26-29	904283W0
STREX system   surface	Black		408-16-18	904284B0
STREX system   surface	White		408-16-18	904284W0
STREX system   suspended	Black		3000	904383B0
STREX system   suspended	White		3000	904383W0

<b>Suspended Remote Driver 100W</b>				
Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system   suspended	Black		150-26-44	904364B0
STREX system   suspended	White		150-26-44	904364W0

<b>Suspended Remote Driver 150W</b>				
Type	Colour	Voltage	L·W·H (MM)	Item number
STREX system   suspended	Black		150-26-44	904374B0
STREX system   suspended	White		150-26-44	904374W0


**Suspended Remote Driver 250W**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   suspended	Black		150-26-44	904384B0
STREX system   suspended	White		150-26-44	904384W0

**TRACKS**
**Track Profile 1m**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   recessed	Black		1000-37-33	904111B0
STREX system   custom cut   recessed	Black		200-999-37-33	904111BOCC
STREX system   recessed	White		1000-37-33	904111W0
STREX system   custom cut   recessed	White		200-999-37-33	904111WOCC
STREX system   surface/suspended	Black		1000-26-29	904211B0
STREX system   custom cut   surface/suspended	Black		200-999-26-29	904211BOCC
STREX system   surface/suspended	White		1000-26-29	904211W0
STREX system   custom cut   surface/suspended	White		200-999-26-29	904211WOCC

**Track Profile 2m**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   recessed	Black		2000-37-33	904112B0
STREX system   custom cut   recessed	Black		1001-1999-37-33	904112BOCC
STREX system   recessed	White		2000-37-33	904112W0
STREX system   custom cut   recessed	White		1001-1999-37-33	904112WOCC
STREX system   surface/suspended	Black		2000-26-29	904212B0
STREX system   custom cut   surface/suspended	Black		1001-1999-26-29	904212BOCC
STREX system   surface/suspended	Aluminium Brushed		2000-26-29	904212L0
STREX system   custom cut   surface/suspended	Aluminium Brushed		1001-1999-26-29	904212LOCC
STREX system   surface/suspended	Champagne		2000-26-29	904212M0
STREX system   custom cut   surface/suspended	Champagne		1001-1999-26-29	904212MOCC
STREX system   surface/suspended	Bronze		2000-26-29	904212Q0
STREX system   custom cut   surface/suspended	Bronze		1001-1999-26-29	904212QOCC
STREX system   surface/suspended	White		2000-26-29	904212W0
STREX system   custom cut   surface/suspended	White		1001-1999-26-29	904212WOCC
STREX system   suspended indirect light	Black		2000-26-29	904512B5
STREX system   custom cut   suspended indirect light	Black		1000-1999-26-29	904512B5CC
STREX system   suspended indirect light	White		2000-26-29	904512W5
STREX system   custom cut   suspended indirect light	White		1000-1999-26-29	904512W5CC


**Track Profile 3m**

Type	Colour	Voltage	L-W-H (MM)	Item number
STREX system   recessed	Black		3000-37-33	904113B0
STREX system   custom cut   recessed	Black		2001-2999-37-33	904113BOCC
STREX system   recessed	White		3000-37-33	904113W0
STREX system   custom cut   recessed	White		2001-2999-37-33	904113WOCC
STREX system   surface/suspended	Black		3000-26-29	904213B0
STREX system   custom cut   surface/suspended	Black		2001-2999-26-29	904213BOCC
STREX system   surface/suspended	Aluminium Brushed		3000-26-29	904213L0
STREX system   custom cut   surface/suspended	Aluminium Brushed		2001-2999-26-29	904213LOCC
STREX system   surface/suspended	Champagne		3000-26-29	904213M0
STREX system   custom cut   surface/suspended	Champagne		2001-2999-26-29	904213MOCC
STREX system   surface/suspended	Bronze		3000-26-29	904213Q0
STREX system   custom cut   surface/suspended	Bronze		2001-2999-26-29	904213QOCC
STREX system   surface/suspended	White		3000-26-29	904213W0
STREX system   custom cut   surface/suspended	White		2001-2999-26-29	904213WOCC
STREX system   suspended indirect light	Black		3000-26-29	904513B5
STREX system   custom cut   suspended indirect light	Black		2001-2999-26-29	904513B5CC
STREX system   suspended indirect light	White		3000-26-29	904513W5
STREX system   custom cut   suspended indirect light	White		2001-2999-26-29	904513W5CC