




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Ceiling surface spotlight made from die-cast aluminium; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 30°; 350° rotatable and 90° tiltable; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



LUMINAIRE

Ceiling _____

Surface _____

tilt max 90 ° _____

rotation 350 ° _____

Black Matt + Aluminium _____

Brushed _____

RAL 9011 ^a _____

IP20 _____

Interior _____

580 lm _____

LED Module

3000 K _____

CRI ≥ 90 _____

L80 / 50000h _____

≤ 2 SDCM (initial MacAdam) _____

Optical

Medium (standard) _____

beam angle 30° _____

CIE flux code: 97 100 100 100 _____

100 _____

Electrical

phase-cut dim _____

220 - 240 V _____

system 8.7 W _____

Class I _____

Standard _____

Physical

length 140 mm _____

width 26 mm _____

height 117 mm _____


0.24 kg _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



177154BL5



CONE DIAGRAM

medium (standard) 31°

h (m)	EO° (lx)	ø (m)
1	1610	0.56
2	400	1.12
3	180	1.67
4	100	2.23
5	60	2.79