



WEVER & DUCRÉ  
LIGHTING

# MATCH on STREX 1.0

179152BL5

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling, Track

Tilt max 90°

Rotation 360°

Black Matt + Aluminium

IP20

Interior

Output: 560 lm

CIE flux code: 97 100 100 100 100

## LED

3000 K

CRI ≥ 90

L80 / 50000h

2 SDCM

## OPTICAL

Medium, Beam angle 30°

## ELECTRICAL

non dim

48 V

LED Inset 7.0 W

Class 3

## PHYSICAL

Diameter 26 mm

Height 117 mm


0.14 kg

115 (adapter) mm

incl. Strex 48 V track adapter



48V track spotlight made from die-cast aluminium; surface Black Matt + Aluminium; powder coated; matt texture; polycarbonate track adapter in Signal Black; inner ring black; spotlight head 360° rotatable and 90° tiltable; beam angle 30°; with COB (Chip on Board) technology for maximum efficiency; non dim; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; 48 V; degree of protection IP20; PC3; UGR ≤ 19; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;






WEVER & DUCRÉ  
LIGHTING

# MATCH

## on STREX 1.0

179152BL5

### LIGHT DISTRIBUTION



### CONE DIAGRAM

medium 30°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 1630     | 0.54  |
| 2     | 410      | 1.09  |
| 3     | 180      | 1.63  |
| 4     | 100      | 2.18  |
| 5     | 70       | 2.72  |

### ELECTRICAL

#### In Track Driver 100W

| TYPE                     | COLOUR            | L · W · H (MM) | ORDERCODE       |
|--------------------------|-------------------|----------------|-----------------|
| STREX system   surface   | Black             | 438-16-18      | 9 0 0 1 4 1 4 3 |
| STREX system   surface   | White             | 438-16-18      | 9 0 0 1 4 1 4 4 |
| STREX system   suspended | White             | 3000           | 9 0 0 1 4 1 5 7 |
| STREX system   suspended | Black             | 3000           | 9 0 0 1 4 1 7 4 |
| STREX system   surface   | Black             | 468-26-29      | 9 0 0 1 4 1 7 6 |
| STREX system   surface   | White             | 468-26-29      | 9 0 0 1 4 1 7 8 |
| STREX system   surface   | Bronze + Black    | 468-26-29      | 9 0 0 1 4 3 7 6 |
| STREX system   surface   | Champagne + Black | 468-26-29      | 9 0 0 1 4 3 7 8 |

#### In Track Driver 250W

| TYPE                     | COLOUR            | L · W · H (MM) | ORDERCODE       |
|--------------------------|-------------------|----------------|-----------------|
| STREX system   surface   | Black             | 408-16-18      | 9 0 0 1 4 1 4 5 |
| STREX system   surface   | White             | 408-16-18      | 9 0 0 1 4 1 4 6 |
| STREX system   suspended | White             | 3000           | 9 0 0 1 4 1 5 8 |
| STREX system   suspended | Black             | 3000           | 9 0 0 1 4 1 7 5 |
| STREX system   surface   | Black             | 438-26-29      | 9 0 0 1 4 1 7 7 |
| STREX system   surface   | White             | 438-26-29      | 9 0 0 1 4 1 7 9 |
| STREX system   surface   | Bronze + Black    | 438-26-29      | 9 0 0 1 4 3 7 7 |
| STREX system   surface   | Champagne + Black | 438-26-29      | 9 0 0 1 4 3 7 9 |

#### Power Feed

| TYPE         | COLOUR | L · H (MM) | ORDERCODE       |
|--------------|--------|------------|-----------------|
| STREX system | White  | 112-18     | 9 0 0 1 4 1 5 3 |
| STREX system | Black  | 112-18     | 9 0 0 1 4 1 5 4 |

[179152BL5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · [www.weverducre.com](http://www.weverducre.com)

# MATCH

## on STREX 1.0

179152BL5

### Connector

| TYPE         | COLOUR | L · H (MM) | ORDERCODE       |
|--------------|--------|------------|-----------------|
| STREX system | White  | 105-18     | 9 0 0 1 4 1 9 6 |
| STREX system | Black  | 105-18     | 9 0 0 1 4 1 9 7 |

### L-Connector

| TYPE                             | COLOUR            | L · W · H (MM) | ORDERCODE       |
|----------------------------------|-------------------|----------------|-----------------|
| STREX system   surface/suspended | White             | 105-105-19     | 9 0 0 1 4 1 9 8 |
| STREX system   surface/suspended | Black             | 105-105-19     | 9 0 0 1 4 1 9 9 |
| STREX system   recessed          | White             | 105-105-19     | 9 0 0 1 4 2 5 1 |
| STREX system   recessed          | Black             | 105-105-19     | 9 0 0 1 4 2 5 2 |
| STREX system   surface/suspended | Champagne + Black | 105-105-19     | 9 0 0 1 4 3 9 8 |
| STREX system   surface/suspended | Bronze + Black    | 105-105-19     | 9 0 0 1 4 3 9 9 |

### T-Connector

| TYPE                   | COLOUR | L · W · H (MM) | ORDERCODE       |
|------------------------|--------|----------------|-----------------|
| STREX system   surface | White  | 275-146-18     | 9 0 0 1 4 2 9 2 |
| STREX system   surface | Black  | 275-146-18     | 9 0 0 1 4 2 9 3 |

### X-Connector

| TYPE                   | COLOUR | L · W · H (MM) | ORDERCODE       |
|------------------------|--------|----------------|-----------------|
| STREX system   surface | Black  | 275-275-18     | 9 0 0 1 4 2 9 4 |
| STREX system   surface | White  | 275-275-18     | 9 0 0 1 4 2 9 5 |

### In Line Driver 100W

| TYPE                     | COLOUR | L · W · H (MM) | ORDERCODE       |
|--------------------------|--------|----------------|-----------------|
| STREX system   suspended | White  | 439-26-44      | 9 0 0 1 4 3 6 0 |
| STREX system   suspended | Black  | 439-26-44      | 9 0 0 1 4 3 6 1 |
| STREX system   surface   | White  | 439-26-44      | 9 0 0 1 4 3 6 6 |
| STREX system   surface   | Black  | 439-26-44      | 9 0 0 1 4 3 6 7 |

### In Line Driver 150W

| TYPE                     | COLOUR | L · W · H (MM) | ORDERCODE       |
|--------------------------|--------|----------------|-----------------|
| STREX system   suspended | White  | 439-26-44      | 9 0 0 1 4 3 6 2 |
| STREX system   suspended | Black  | 439-26-44      | 9 0 0 1 4 3 6 3 |
| STREX system   surface   | White  | 439-26-44      | 9 0 0 1 4 3 7 0 |
| STREX system   surface   | Black  | 439-26-44      | 9 0 0 1 4 3 7 1 |

### Ceiling Driver 100W

| TYPE                     | COLOUR | L · W · H (MM) | ORDERCODE       |
|--------------------------|--------|----------------|-----------------|
| STREX system   suspended | White  | 439-26-44      | 9 0 0 1 4 3 6 8 |
| STREX system   suspended | Black  | 439-26-44      | 9 0 0 1 4 3 6 9 |

### Ceiling Driver 150W

| TYPE                     | COLOUR | L · W · H (MM) | ORDERCODE       |
|--------------------------|--------|----------------|-----------------|
| STREX system   suspended | White  | 439-26-44      | 9 0 0 1 4 3 7 2 |
| STREX system   suspended | Black  | 439-26-44      | 9 0 0 1 4 3 7 3 |

# MATCH on STREX 1.0

179152BL5

## DALI Selv Device

| TYPE         | L · W · H (MM) | ORDERCODE       |
|--------------|----------------|-----------------|
| STREX system | 213·37·25      | 9 0 0 1 9 1 9 3 |



## Driver

| TYPE                | L · W · H (MM) | ORDERCODE       |
|---------------------|----------------|-----------------|
| STREX system   100W | 350·30·18      | 9 0 2 1 8 9 0 1 |
| STREX system   150W | 350·30·18      | 9 0 2 1 8 9 0 2 |
| STREX system   250W | 400·40·22      | 9 0 2 1 8 9 0 3 |

## SUSPENDED

### Track Profile 2m

| TYPE                                                 | COLOUR | L · W · H (MM)  | ORDERCODE           |
|------------------------------------------------------|--------|-----------------|---------------------|
| STREX system   suspended indirect light              | Black  | 2000·26·29      | 9 0 0 1 4 0 B 5     |
| STREX system   custom cut   suspended indirect light | Black  | 1000·1999·26·29 | 9 0 0 1 4 0 B 5 C C |
| STREX system   suspended indirect light              | White  | 2000·26·29      | 9 0 0 1 4 0 W 5     |
| STREX system   custom cut   suspended indirect light | White  | 1000·1999·26·29 | 9 0 0 1 4 0 W 5 C C |

### Suspension Set

| TYPE                            | COLOUR          | L · W · H (MM) | ORDERCODE       |
|---------------------------------|-----------------|----------------|-----------------|
| STREX system   1.5m   suspended | Stainless Steel | 80·23·1500     | 9 0 0 1 4 1 6 0 |
| STREX system   3.0m   suspended | Stainless Steel | 80·23·3000     | 9 0 0 1 4 1 6 1 |
| STREX system   1.5m   suspended | Black           | 80·23·1500     | 9 0 0 1 4 2 7 4 |
| STREX system   3.0m   suspended | Black           | 80·23·3000     | 9 0 0 1 4 2 7 5 |

### Track Profile 3m

| TYPE                                                 | COLOUR | L · W · H (MM)  | ORDERCODE           |
|------------------------------------------------------|--------|-----------------|---------------------|
| STREX system   suspended indirect light              | Black  | 3000·26·29      | 9 0 0 1 4 1 B 5     |
| STREX system   custom cut   suspended indirect light | Black  | 2001·2999·26·29 | 9 0 0 1 4 1 B 5 C C |
| STREX system   suspended indirect light              | White  | 3000·26·29      | 9 0 0 1 4 1 W 5     |
| STREX system   custom cut   suspended indirect light | White  | 2001·2999·26·29 | 9 0 0 1 4 1 W 5 C C |

## COVER

### Blank Cover 2m

| TYPE         | COLOUR | L · W · H (MM) | ORDERCODE       |
|--------------|--------|----------------|-----------------|
| STREX system | Black  | 2000·18·3      | 9 1 1 0 0 2 B 0 |
| STREX system | White  | 2000·18·3      | 9 1 1 0 0 2 W 0 |

# MATCH on STREX 1.0

179152BL5

## RECESSED

### End Cap

| TYPE                    | COLOUR | L · W · H (MM) | ORDERCODE       |
|-------------------------|--------|----------------|-----------------|
| STREX system   recessed | White  | 37·10·27       | 9 0 0 1 4 1 4 9 |
| STREX system   recessed | Black  | 37·10·27       | 9 0 0 1 4 1 5 0 |

### Track Profile 1m

| TYPE                                 | COLOUR | L · W · H (MM) | ORDERCODE           |
|--------------------------------------|--------|----------------|---------------------|
| STREX system   recessed              | White  | 1000·37·33     | 9 0 0 1 4 1 8 7     |
| STREX system   custom cut   recessed | White  | 200-999·37·33  | 9 0 0 1 4 1 8 7 C C |
| STREX system   recessed              | Black  | 1000·37·33     | 9 0 0 1 4 1 8 8     |
| STREX system   custom cut   recessed | Black  | 200-999·37·33  | 9 0 0 1 4 1 8 8 C C |

### Track Profile 2m

| TYPE                                 | COLOUR | L · W · H (MM)  | ORDERCODE           |
|--------------------------------------|--------|-----------------|---------------------|
| STREX system   recessed              | White  | 2000·37·33      | 9 0 0 1 4 1 8 9     |
| STREX system   custom cut   recessed | White  | 1001-1999·37·33 | 9 0 0 1 4 1 8 9 C C |
| STREX system   recessed              | Black  | 2000·37·33      | 9 0 0 1 4 1 9 0     |
| STREX system   custom cut   recessed | Black  | 1001-1999·37·33 | 9 0 0 1 4 1 9 0 C C |

### Track Profile 3m

| TYPE                                 | COLOUR | L · W · H (MM)  | ORDERCODE           |
|--------------------------------------|--------|-----------------|---------------------|
| STREX system   recessed              | White  | 3000·37·33      | 9 0 0 1 4 1 9 1     |
| STREX system   custom cut   recessed | White  | 2001-2999·37·33 | 9 0 0 1 4 1 9 1 C C |
| STREX system   recessed              | Black  | 3000·37·33      | 9 0 0 1 4 1 9 2     |
| STREX system   custom cut   recessed | Black  | 2001-2999·37·33 | 9 0 0 1 4 1 9 2 C C |

### Mounting Bracket

| TYPE                    | ORDERCODE       |
|-------------------------|-----------------|
| STREX system   recessed | 9 0 0 1 4 1 9 3 |

### L-Connector non-electrical

| TYPE                    | COLOUR | L · W · H (MM) | ORDERCODE       |
|-------------------------|--------|----------------|-----------------|
| STREX system   recessed | White  | 105·105·19     | 9 0 0 1 4 2 5 6 |
| STREX system   recessed | Black  | 105·105·19     | 9 0 0 1 4 2 5 7 |

## SURFACE

### End Cap

| TYPE                             | COLOUR    | L · W · H (MM) | ORDERCODE       |
|----------------------------------|-----------|----------------|-----------------|
| STREX system   surface/suspended | White     | 26·2.5·29      | 9 0 0 1 4 1 4 7 |
| STREX system   surface/suspended | Black     | 26·2.5·29      | 9 0 0 1 4 1 4 8 |
| STREX system   surface/suspended | Champagne | 26·2.5·29      | 9 0 0 1 4 3 4 7 |
| STREX system   surface/suspended | Bronze    | 26·2.5·29      | 9 0 0 1 4 3 4 8 |

# MATCH

## on STREX 1.0

179152BL5

### Track Profile 1m

| TYPE                                          | COLOUR | L · W · H (MM) | ORDERCODE           |
|-----------------------------------------------|--------|----------------|---------------------|
| STREX system   surface/suspended              | White  | 1000-26-29     | 9 0 0 1 4 1 8 1     |
| STREX system   custom cut   surface/suspended | White  | 200-999-26-29  | 9 0 0 1 4 1 8 1 C C |
| STREX system   surface/suspended              | Black  | 1000-26-29     | 9 0 0 1 4 1 8 2     |
| STREX system   custom cut   surface/suspended | Black  | 200-999-26-29  | 9 0 0 1 4 1 8 2 C C |

### Track Profile 2m

| TYPE                                          | COLOUR    | L · W · H (MM)  | ORDERCODE           |
|-----------------------------------------------|-----------|-----------------|---------------------|
| STREX system   surface/suspended              | White     | 2000-26-29      | 9 0 0 1 4 1 8 3     |
| STREX system   custom cut   surface/suspended | White     | 1001-1999-26-29 | 9 0 0 1 4 1 8 3 C C |
| STREX system   surface/suspended              | Black     | 2000-26-29      | 9 0 0 1 4 1 8 4     |
| STREX system   custom cut   surface/suspended | Black     | 1001-1999-26-29 | 9 0 0 1 4 1 8 4 C C |
| STREX system   surface/suspended              | Champagne | 2000-26-29      | 9 0 0 1 4 3 8 3     |
| STREX system   custom cut   surface/suspended | Champagne | 1001-1999-26-29 | 9 0 0 1 4 3 8 3 C C |
| STREX system   surface/suspended              | Bronze    | 2000-26-29      | 9 0 0 1 4 3 8 4     |
| STREX system   custom cut   surface/suspended | Bronze    | 1001-1999-26-29 | 9 0 0 1 4 3 8 4 C C |

### Track Profile 3m

| TYPE                                          | COLOUR    | L · W · H (MM)  | ORDERCODE           |
|-----------------------------------------------|-----------|-----------------|---------------------|
| STREX system   surface/suspended              | White     | 3000-26-29      | 9 0 0 1 4 1 8 5     |
| STREX system   custom cut   surface/suspended | White     | 2001-2999-26-29 | 9 0 0 1 4 1 8 5 C C |
| STREX system   surface/suspended              | Black     | 3000-26-29      | 9 0 0 1 4 1 8 6     |
| STREX system   custom cut   surface/suspended | Black     | 2001-2999-26-29 | 9 0 0 1 4 1 8 6 C C |
| STREX system   surface/suspended              | Champagne | 3000-26-29      | 9 0 0 1 4 3 8 5     |
| STREX system   custom cut   surface/suspended | Champagne | 2001-2999-26-29 | 9 0 0 1 4 3 8 5 C C |
| STREX system   surface/suspended              | Bronze    | 3000-26-29      | 9 0 0 1 4 3 8 6     |
| STREX system   custom cut   surface/suspended | Bronze    | 2001-2999-26-29 | 9 0 0 1 4 3 8 6 C C |

### L-Connector non-electrical

| TYPE                   | COLOUR         | L · W · H (MM) | ORDERCODE       |
|------------------------|----------------|----------------|-----------------|
| STREX system   surface | White          | 105-105-19     | 9 0 0 1 4 2 5 8 |
| STREX system   surface | Black          | 105-105-19     | 9 0 0 1 4 2 5 9 |
| STREX system   surface | Gold + Black   | 105-105-19     | 9 0 0 1 4 4 5 8 |
| STREX system   surface | Bronze + Black | 105-105-19     | 9 0 0 1 4 4 5 9 |