



PROJECT

TYPE


NOTES

QUANTITY

DATE



Pendant rod suspension made from aluminium; can be cut and adjusted as desired max. 1950 mm; for ceiling surface mounting; surface Black Matt + Champagne; powder coated; matt texture + wet painted; smooth semi glossy; No matching RAL; opal PMMA diffuser; PCB 3-step binning; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; CRI (Colour Rendering Index) ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Ceiling _____
 Surface _____
 Black Matt + Champagne _____
 No matching RAL _____
 IP20 _____
 Interior _____
 730 lm _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 ≤ 3 SDCM (initial MacAdam) _____
 980 lm _____
 178 lm/W^a _____

Optical

Opal _____
 CIE flux code: 11 35 66 50 100 _____

Electrical

phase-cut dim _____
 220 - 240 V _____
 system 7.3 W _____
 Class I _____
 Standard _____

Physical


diameter 9 mm _____
 height 1000 mm _____
 0.43 kg _____

datasheet.quicksum.material

Aluminium _____

^a Without electrical and optical losses

LIGHT DISTRIBUTION



[174284CH5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.96	0.94	0.93	0.91
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING ACCESSORIES

FINLIN Cover Plate Adapter

Type	Colour	Voltage	Ø·H (MM)	Item number
for concrete housings	Black		100·3	900194B0