




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Oval ceiling recessed downlight made from die-cast aluminium; surface Champagne; powder coated; matt texture; No matching RAL; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 67 mm; beam angle 31°; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90; UGR ≤ 16; degree of protection IP20; Class 3; IC rated; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling _____
 Recessed _____
 Champagne _____
 No matching RAL _____
 IP20 _____
 IC rated _____
 Interior _____
 970 lm / 250mA _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000 h _____
 ≤ 2 SDCM (initial MacAdam) _____
 1140 lm / 250mA _____
 137 lm/W^a _____
 8.3 W^a _____

Optical

Medium (standard) _____
 beam angle 31° _____
 CIE flux code: 99 100 100 100 _____
 100 _____

Electrical

excl. driver _____
 34 V _____
 Class III _____
 Standard _____

Physical

length 107 mm _____
 width 57 mm _____
 height 51 mm _____
 0.15 kg _____
 wire springs _____

Cutout


min. ceiling thickness 4 mm _____
 max. ceiling thickness 25 mm _____
 recessed depth 67 mm _____
 Cut out: 50-52 x 100-104 _____

datasheet.quicksum.material

Aluminium _____

^a Without electrical and optical losses

LIGHT DISTRIBUTION





CONE DIAGRAM

medium (standard) 250mA

h (m)	E0° (lx)	ø (m)
1	2820	0.54
2	710	1.07
3	310	1.61
4	180	2.15
5	110	2.68

Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
10.5W 250mA 26-42V phase-cut dim		26-42V	122-41-23	90226501
10W 250mA 10-40V DALI-2 push dim		10-40V	166-29-21	90246403