




PROJECT

TYPE

NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; surface Champagne wet painted; matt texture; No matching RAL; installation without tools using blade springs; suitable for ceiling thickness of 4-25 mm; recessed depth 85 mm; beam angle 31°; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; UGR ≤ 16 ; degree of protection IP20; Class 3; IC rated; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
 Recessed
 Champagne
 No matching RAL
 IP20
 IC rated
 Interior
 460 lm / 250mA

LED Module

2700 K
 CRI ≥ 90
 L80 / 50000 h
 ≤ 2 SDCM (initial MacAdam)
 540 lm / 250mA
 129 lm/W^a
 4.2 W^a

Optical

Medium (standard)
 beam angle 31°
 CIE flux code: 99 100 100 100
 100

Electrical

excl. driver
 17 V
 Class III
 Standard

Physical

diameter 57 mm
 height 51 mm
 0.07 kg
 blade springs

Cutout


diameter 50-52 mm
 min. ceiling thickness 4 mm
 max. ceiling thickness 25 mm
 recessed depth 85 mm

datasheet.quicksum.material

Aluminium

^a Without electrical and optical losses

LIGHT DISTRIBUTION





CONE DIAGRAM

medium (standard) 250mA

h (m)	E0° (lx)	ø (m)
1	1340	0.54
2	330	1.07
3	150	1.61
4	80	2.15
5	50	2.68

Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
5W 250mA 12-21V phase-cut dim		12-21V	68-33-22	90226201
10W 250mA 10-40V DALI-2 push dim		10-40V	166-29-21	90246403