



PROJECT

TYPE


NOTES

QUANTITY

DATE



Ceiling surface luminaire with 2 spotlights; made from die-cast aluminium; surface White Matt; powder coated, matt texture; RAL 9010; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2000 - 3000 K colour warm dimming; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 39°; 355° rotatable and 60° tiltable; degree of protection IP20; Class I; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
 Surface
 tilt max 60 °
 rotation 355 °
 White Matt
 RAL 9010 ^a
 IP20
 Interior
 680 lm

LED Module

colour warm dimming
 2000 - 3000 K
 CRI ≥ 90
 L70 / 50000h
 ≤ 3 SDCM (initial MacAdam)
 340 lm
 96 lm/W ^b

Optical

Medium (standard)
 beam angle 39°
 CIE flux code: 99 100 100 100
 100

Electrical

phase-cut dim
 220 - 240 V
 system 7.1 W
 Class I
 Standard

Physical


length 230 mm
 width 80 mm
 height 66 mm
 0.65 kg

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses

LIGHT DISTRIBUTION



[164664W9] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



CONE DIAGRAM

medium (standard) 31°

h (m)	EO° (lx)	ø (m)
1	979	0.55
2	245	1.11
3	109	1.66
4	61	2.22
5	39	2.77

OPTICAL ACCESSORIES

Honeycomb Louver

Type	Colour	Voltage	Ø (MM)	Item number
BLIEK petit CENO LECA PIRRO QITO	Black		29	915230B0