



WEVER & DUCRÉ
LIGHTING

BLIEK

petit SURFACE 2.0

164664CH9

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Surface

Tilt max 60°

Rotation 355°

Black Matt + Champagne

IP20

Interior

Output: 680 lm

CIE flux code: 99 100 100 100 100

LED

colour warm dimming

2000 K - 3000 K

CRI ≥ 90

L70 / 55000h

3 SDCM

OPTICAL

Medium , Beam angle 39°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 14.2 W

Class 1

PHYSICAL

Length 230 mm


Width 80 mm

Height 66 mm

0.65 kg



Ceiling surface luminaire with 2 spotlights; made from die-cast aluminium; surface Black Matt + Champagne; powder coated; matt texture + wet painted; smooth semi glossy; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2000 K - 3000 K colour warm dimming; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; beam angle 39°; 355° rotatable and 60° tiltable; degree of protection IP20; PC1; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by an authorized professional;




BLIEK

petit SURFACE 2.0

164664CH9

LIGHT DISTRIBUTION



CONE DIAGRAM

medium 31°

h (m)	E0° (lx)	ø (m)
1	1960	0.55
2	490	1.11
3	220	1.66
4	120	2.22
5	80	2.77

OPTICAL

Honeycomb Louver

TYPE	Ø (MM)	ORDERCODE
BLIEK PETIT CENO LECA PIRRO	29	9 0 0 5 1 1 3 1