WEVER & DUCRÉ LIGHTING

BLIEK petit SURFACE 2.0

164664B5

PROJECT

TYPE

NOTES

QUANTITY

DATE

Ceiling surface luminaire with 2 spotlights; made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 1; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Surface
tilt max 60 °
rotation 355 °
Black Matt
RAL 9011 [a]
IP20
Interior
1020 lm

LED Module

3000 K
CRI ≥ 90
L70 / 55000h
≤ 2 SDCM (initial MacAdam)
510 lm
72 lm/W [b]

Optical

Medium (standard)
beam angle 31°
CIE flux code: 99 100 100 100 100

Electrical

phase-cut dim
220 - 240 V
system 14.2 W
Class I
Standard

Physical

length 230 mm
width 80 mm
height 66 mm
0.65 kg

datasheet.quicksum.material

Aluminium

[a] Colour may deviate slightly due to production conditions
[b] Without electrical and optical losses

LIGHT DISTRIBUTION



['164664B5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

CONE DIAGRAM

medium (standard) 31°

h (m)	E0° (lx)	ø (m)
1	1460	0.55
2	370	1.11
3	160	1.66
4	90	2.22
5	60	2.77

OPTICAL ACCESSORIES

Honeycomb Louver

Type	Colour	Voltage	Ø (MM)	Item number
BLIEK petit | CENO | LECA | PIRRO | QITO	Black		29	915230B0

['164664B5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com