



WEVER & DUCRÉ
LIGHTING

BLIEK

petit SURFACE 2.0

164664B3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Surface

Tilt max 60°

Rotation 355°

Black Matt

RAL 9005^a

IP20

Interior

Output: 980 lm

CIE flux code: 99 100 100 100 100

LED

2700 K

CRI ≥ 90

L70 / 55000h

2 SDCM

OPTICAL

Medium, Beam angle 31°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 14.2 W

Class 1

PHYSICAL

Length 230 mm

Width 80 mm


Height 66 mm

0.65 kg


^a Color may deviate slightly due to production conditions.



Ceiling surface luminaire with 2 spotlights; made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; PC1; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION



[164664B3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

BLIEK

petit SURFACE 2.0

164664B3

CONE DIAGRAM

medium 31°

h (m)	EO° (lx)	ø (m)
1	2820	0.55
2	710	1.11
3	310	1.66
4	180	2.22
5	110	2.77

OPTICAL

Honeycomb Louver

TYPE	Ø (MM)	ORDERCODE
BLIEK PETIT CENO LECA PIRRO	29	9 0 0 5 1 1 3 1