

## BLIEK petit SURFACE 2.0

164664B3

- 医格洛特氏线病
5.00204030
CATCHING.
- <del>198</del> 2-298-2989
<b>- 医数据数据数据数据数据</b>
<b>2006/00/00</b>
国际发展级数据:

150°

309

120°

909

LIGHT DISTRIBUTION

3300

C0/C180

#### **PROJECT**

**TYPE** 

**NOTES** 

QUANTITY

DATE












Ceiling surface luminaire with 2 spotlights; made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K;  $\leq$  2 SDCM (initial MacAdam); CRI  $\geq$  90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 1; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



Ducré BV apply.

#### **LUMINAIRE**

Ceiling
Surface
tilt max 60 °
rotation 355 °
Black Matt
RAL 9011 <sup>a</sup>
IP20
Interior
980 lm

### **LED Module**

2700 K
CRI ≥ 90
L70 / 55000h
≤ 2 SDCM (initial MacAdam)
490 lm
69 lm/W <sup>b</sup>

#### **Optical**

Medium (standard)				
beam angle 31°				
CIE flux code: 99 100 100 100				
100				

#### **Electrical**

phase-cut dim
220 - 240 V
system 14.2 W
Class I

#### **Physical**

length 230 mm
width 80 mm
height 66 mm
0.65 kg

<sup>&</sup>lt;sup>a</sup> Colour may deviate slightly due to production conditions

<sup>&</sup>lt;sup>b</sup> Without electrical and optical losses



# BLIEK petit SURFACE 2.0

164664B3



#### **CONE DIAGRAM**

medium (standard) 31°

h (m)	E0° (lx)	ø (m)	
1	1410	0.55	
2	350	1.11	
3	160	1.66	
4	90	2.22	
5	60	2.77	

## **OPTICAL ACCESSORIES**

**Honeycomb Louver** 

Type	Colour	Voltage	Ø (MM)	Item number
BLIEK PETIT   CENO   LECA   PIRRO	Black		29	90051131