



WEVER & DUCRÉ
LIGHTING

BLIEK

ROUND petit trimless 1.0

164561W9

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Semi-Recessed

Tilt max 60°

Rotation 355°

White Matt

IP20

Interior

Output: 340 lm

CIE flux code: 99 100 100 100 100

LED

colour warm dimming

2000 K - 3000 K

CRI ≥ 90

L70 / 50000h

3 SDCM

OPTICAL

Medium , Beam angle 39°

ELECTRICAL

excl. driver

16 V

LED Inset 5.7 W

Class 3

350 mA

PHYSICAL

Diameter 35 mm

Height 55 mm

0.17 kg

alu plasterkit

CUTCUT


Diameter 78-80 mm

Recessed depth 80 mm

12,5, 15,25



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 2000 K - 3000 K colour warm dimming; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; beam angle 39°; 355° rotatable and 60° tiltable; degree of protection IP20; PC3; IC rated; driver not included; to be combined with the plasterkit suitable for ceiling thickness; optional honeycomb louver available, to reduce glare; light source replaceable by an authorized professional;




BLIEK

ROUND petit trimless 1.0

164561W9

LIGHT DISTRIBUTION



CONE DIAGRAM

medium 30° 350mA

h (m)	E0° (lx)	ø (m)
1	1000	0.54
2	250	1.09
3	110	1.63
4	60	2.17
5	40	2.71

OPTICAL

Honeycomb Louver

TYPE	Ø (MM)	ORDERCODE
BLIEK PETIT CENO LECA PIRRO	29	9 0 0 5 1 1 3 1

MOUNTING

Plasterkit

TYPE	Ø · H (MM)	ORDERCODE
BLIEK PETIT TRIMLESS	Ø73-29	9 0 0 1 7 2 1 0

ELECTRICAL

Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
6W 350mA	67·39·22	8.6-18V	9 0 2 1 3 3 0 3
10W 350mA 1-10V dim	101.5·51·29.5	14-28V	9 0 2 2 3 4 0 1
10W 350mA phase-cut dim	102·38·21	12-28V	9 0 2 2 3 4 0 2
15W 700mA 12-20V phase-cut dim	122·41·23	12-20V	9 0 2 2 5 5 0 2
14W 350mA	145·33·21	2.5-42V	9 0 2 4 3 5 0 1
17W 350mA 10-49V DALI	108·52·22	10-49V	9 0 2 4 3 6 0 1