



WEVER & DUCRÉ  
LIGHTING

# BLIEK ROUND petit trimless 1.0

164561W3

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling , Semi-Recessed

Tilt max 60°

Rotation 355°

White Matt

IP20

IC rated

Interior

Output: 495 lm

CIE flux code: 99 100 100 100 100

## LED

2700 K

CRI ≥ 90

L70 / 55000h

2 SDCM

## OPTICAL

Medium , Beam angle 31°

## ELECTRICAL

excl. driver

17 V

LED Inset 6.0 W

Class 3

350 mA

## PHYSICAL

Diameter 35 mm

Height 55 mm

0.17 kg

alu plasterkit

## CUTOUT


Diameter 78-80 mm

Recessed depth 80 mm

12,5, 15,25



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; PC3; IC rated; driver not included; to be combined with the plasterkit suitable for ceiling thickness; optional honeycomb louver available, to reduce glare; light source replaceable by an authorized professional;




# BLIEK

## ROUND petit trimless 1.0

164561W3

### LIGHT DISTRIBUTION



### CONE DIAGRAM

medium 30° 350mA

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 1460     | 0.54  |
| 2     | 360      | 1.09  |
| 3     | 160      | 1.63  |
| 4     | 90       | 2.17  |
| 5     | 60       | 2.71  |

### OPTICAL

#### Honeycomb Louver

| TYPE                              | Ø (MM) | ORDERCODE       |
|-----------------------------------|--------|-----------------|
| BLIEK PETIT   CENO   LECA   PIRRO | 29     | 9 0 0 5 1 1 3 1 |

### MOUNTING

#### Plasterkit

| TYPE                 | Ø · H (MM) | ORDERCODE       |
|----------------------|------------|-----------------|
| BLIEK PETIT TRIMLESS | Ø73-29     | 9 0 0 1 7 2 1 0 |

### ELECTRICAL

#### Driver

| TYPE                                 | L · W · H (MM) | VOLTAGE | ORDERCODE       |
|--------------------------------------|----------------|---------|-----------------|
| 6W   350mA                           | 67·39·22       | 8.6-18V | 9 0 2 1 3 3 0 3 |
| 10W   350mA   1-10V dim              | 101.5·51·29.5  | 14-28V  | 9 0 2 2 3 4 0 1 |
| 10W   350mA   phase-cut dim          | 102·38·21      | 12-28V  | 9 0 2 2 3 4 0 2 |
| 15W   700mA   12-20V   phase-cut dim | 122·41·23      | 12-20V  | 9 0 2 2 5 5 0 2 |
| 14W   350mA                          | 145·33·21      | 2.5-42V | 9 0 2 4 3 5 0 1 |
| 17W   350mA   10-49V   DALI          | 108·52·22      | 10-49V  | 9 0 2 4 3 6 0 1 |