



WEVER & DUCRÉ  
LIGHTING

# BLIEK

## ROUND petit trimless 1.0

164561B9

Project

Type

Notes

Quantity

Date

### GENERAL

Ceiling , Semi-Recessed

Tilt max 60°

Rotation 355°

Black Matt

RAL 9005 <sup>a</sup>

IP20

Interior

Output: 340 lm

CIE flux code: 99 100 100 100 100

### LED

colour warm dimming

2000 K - 3000 K

CRI ≥ 90

L70 / 50000h

3 SDCM

### OPTICAL

Medium , Beam angle 39°

### ELECTRICAL

excl. driver

16 V

LED Inset 5.7 W

Class 3

350 mA

### PHYSICAL

Diameter 35 mm

Height 55 mm

0.17 kg

alu plasterkit

### CUTOUT

Diameter 78-80 mm


Recessed depth 80 mm

12,5, 15,25

<sup>a</sup> Color may deviate slightly due to production conditions.



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; RAL 9005; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 2000 K - 3000 K colour warm dimming; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; beam angle 39°; 355° rotatable and 60° tiltable; degree of protection IP20; PC3; IC rated; driver not included; to be combined with the plasterkit suitable for ceiling thickness; optional honeycomb louver available, to reduce glare; light source replaceable by an authorized professional;






WEVER & DUCRÉ  
LIGHTING

# BLIEK ROUND petit trimless 1.0

164561B9

## LIGHT DISTRIBUTION



## CONE DIAGRAM

medium 30° 350mA

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 1000     | 0.54  |
| 2     | 250      | 1.09  |
| 3     | 110      | 1.63  |
| 4     | 60       | 2.17  |
| 5     | 40       | 2.71  |

## OPTICAL

### Honeycomb Louver

| TYPE                              | Ø (MM) | ORDERCODE       |
|-----------------------------------|--------|-----------------|
| BLIEK PETIT   CENO   LECA   PIRRO | 29     | 9 0 0 5 1 1 3 1 |

## MOUNTING

### Plasterkit

| TYPE                 | Ø · H (MM) | ORDERCODE       |
|----------------------|------------|-----------------|
| BLIEK PETIT TRIMLESS | Ø73-29     | 9 0 0 1 7 2 1 0 |

## ELECTRICAL

### Driver

| TYPE                                 | L · W · H (MM) | VOLTAGE | ORDERCODE       |
|--------------------------------------|----------------|---------|-----------------|
| 6W   350mA                           | 67-39-22       | 8.6-18V | 9 0 2 1 3 3 0 3 |
| 10W   350mA   1-10V dim              | 101.5-51-29.5  | 14-28V  | 9 0 2 2 3 4 0 1 |
| 10W   350mA   phase-cut dim          | 102-38-21      | 12-28V  | 9 0 2 2 3 4 0 2 |
| 15W   700mA   12-20V   phase-cut dim | 122-41-23      | 12-20V  | 9 0 2 2 5 5 0 2 |
| 14W   350mA                          | 145-33-21      | 2.5-42V | 9 0 2 4 3 5 0 1 |
| 17W   350mA   10-49V   DALI          | 108-52-22      | 10-49V  | 9 0 2 4 3 6 0 1 |