



PROJECT

---

TYPE

---

NOTES

---

QUANTITY


---

DATE

---



Rectangular ceiling recessed downlight made from die-cast aluminium; surface White Matt + Champagne; RAL 9010 + No matching RAL; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K;  $\leq 3$  SDCM (initial MacAdam); CRI  $\geq 90$ ; beam angle 28°; degree of protection IP20; Class 3; IC rated; UGR  $\leq 13$ ; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**LUMINAIRE**

Ceiling  
 Recessed  
 White Matt + Champagne  
 RAL 9010 + No matching RAL  
 a  
 IP20  
 IC rated  
 Interior  
 1000 lm

**LED Module**

3000 K  
 CRI  $\geq 90$   
 L80 / 50000h  
 $\leq 3$  SDCM (initial MacAdam)

**Optical**

Medium (standard)  
 beam angle 28°  
 CIE flux code: 98 100 100 100  
 100

**Electrical**

excl. driver  
 36 V  
 Class III  
 Standard

**Physical**

length 172 mm  
 width 40 mm  
 height 40 mm  
 0.15 kg  
 wire springs

**Cutout**


length 168 mm  
 width 33 mm  
 min. ceiling thickness 4 mm  
 max. ceiling thickness 25 mm  
 recessed depth 60 mm

**datasheet.quicksum.material**

Aluminium

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**





**CONE DIAGRAM**

medium (standard) 25°

h (m)	E0° (lx)	ø (m)
1	3880	0.45
2	970	0.90
3	430	1.35
4	240	1.81
5	160	2.26

**ELECTRICAL ACCESSORIES**

**Driver**

Type	Colour	Voltage	L·W·H (MM)	Item number
13W   350mA   26-38V   phase-cut dim		26-38V	138-44-30	90223404
14W   350mA   10-40V   DALI-2 push dim		10-40V	166-29-21	90243502