



WEVER & DUCRÉ  
LIGHTING

# PIRRO petit 6.0

129351B3

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling , Recessed

Black Matt

RAL 9005 <sup>a</sup>

IP20

IC rated

Interior

Output: 870 lm

CIE flux code: 98 100 100 100 100

## LED

2700 K

CRI  $\geq$  90

L80 / 50000h

3 SDCM

## OPTICAL

Medium , Beam angle 28°

## ELECTRICAL

excl. driver

36 V

LED Inset 11.4 W

Class 3

350 mA

## PHYSICAL

Length 172 mm

Width 40 mm

Height 40 mm

0.15 kg

wire springs

## CUTOUT

Length 168 mm


Width 33 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 25 mm

Recessed depth 60 mm

<sup>a</sup> Color may deviate slightly due to production conditions.



Rectangular ceiling recessed downlight made from die-cast aluminium; surface Black Matt; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  90; beam angle 28°; degree of protection IP20; PC3; IC rated; UGR  $\leq$  13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65°  $\leq$  3000 cd/m<sup>2</sup>; driver not included; light source replaceable by an authorized professional;




PIRRO

petit 6.0

129351B3

LIGHT DISTRIBUTION



CONE DIAGRAM

medium 25°

h (m)	E0° (lx)	ø (m)
1	3370	0.45
2	840	0.90
3	370	1.35
4	210	1.81
5	130	2.26

ELECTRICAL

Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
15W   350 mA   27-42V   phase-cut dim	102 · 49 · 29	27-42V	9 0 2 2 3 4 0 3
14.7W   350mA   26-42V	122 · 41 · 23	26-42V	9 0 2 2 3 5 0 4