



**PROJECT** \_\_\_\_\_

---

**TYPE** \_\_\_\_\_

---

**NOTES** \_\_\_\_\_

---

**QUANTITY** \_\_\_\_\_


---

**DATE** \_\_\_\_\_

---



Rectangular ceiling recessed downlight made from die-cast aluminium; surface Black Matt + Champagne; RAL 9011 + No matching RAL; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K;  $\leq 3$  SDCM (initial MacAdam); CRI  $\geq 90$ ; beam angle 28°; degree of protection IP20; Class 3; IC rated; UGR  $\leq 13$ ; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**LUMINAIRE**

Ceiling \_\_\_\_\_  
 Recessed \_\_\_\_\_  
 Black Matt + Champagne \_\_\_\_\_  
 RAL 9011 + No matching RAL <sup>a</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 IC rated \_\_\_\_\_  
 Interior \_\_\_\_\_  
 640 lm \_\_\_\_\_

**LED Module**

2700 K \_\_\_\_\_  
 CRI  $\geq 90$  \_\_\_\_\_  
 L80 / 50000h \_\_\_\_\_  
 $\leq 3$  SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

Medium (standard) \_\_\_\_\_  
 beam angle 28° \_\_\_\_\_  
 CIE flux code: 98 100 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_  
 24 V \_\_\_\_\_  
 Class III \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**

length 119 mm \_\_\_\_\_  
 width 40 mm \_\_\_\_\_  
 height 40 mm \_\_\_\_\_  
 0.1 kg \_\_\_\_\_  
 wire springs \_\_\_\_\_

**Cutout**


length 116 mm \_\_\_\_\_  
 width 33 mm \_\_\_\_\_  
 min. ceiling thickness 4 mm \_\_\_\_\_  
 max. ceiling thickness 25 mm \_\_\_\_\_  
 recessed depth 60 mm \_\_\_\_\_

**datasheet.quicksum.material**

Aluminium \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**





**CONE DIAGRAM**

medium (standard) 25°

h (m)	E0° (lx)	ø (m)
1	2480	0.45
2	620	0.90
3	280	1.35
4	160	1.81
5	100	2.26

**ELECTRICAL ACCESSORIES**

**Driver**

Type	Colour	Voltage	L·W·H (MM)	Item number
10W   350mA   13-26V   phase-cut dim		13-26V	115-41-25	90223406
14W   350mA   10-40V   DALI-2 push dim		10-40V	166-29-21	90243502