



WEVER & DUCRÉ
LIGHTING

PIRRO

petit SURFACE 12.0

129954B5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Surface

Black Matt

RAL 9005 ^a

IP20

Interior

Output: 1810 lm

CIE flux code: 98 100 100 100 100

LED

3000 K

CRI ≥ 90

L80 / 50000h

3 SDCM

OPTICAL

Medium , Beam angle 28°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 26.8 W

Class I

PHYSICAL


Length 322 mm

Width 31 mm


Height 50 mm

0.38 kg

^a Color may deviate slightly due to production conditions.



Rectangular ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; beam angle 28°; degree of protection IP20; PC1; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; driver included; light source replaceable by an authorized professional; control gear replaceable by end-user;




PIRRO

petit SURFACE 12.0

129954B5

LIGHT DISTRIBUTION



CONE DIAGRAM

medium 25°

h (m)	E0° (lx)	ø (m)
1	7020	0.45
2	1750	0.90
3	780	1.35
4	440	1.81
5	280	2.26