



PROJECT

TYPE

NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; surface Champagne; wet painted, smooth semi glossy; No matching RAL; installation without tools using wire springs; suitable for ceiling thickness of 4-27 mm; recessed depth 90mm; lamp socket GU5.3; lamp type QR-CBC51; max. 12W; 12 V; degree of protection IP20; Class 3; driver not included; lamp not included;

GENERAL

Ceiling
Recessed
Champagne
No matching RAL
IP20
Interior

LED

lamp QR-CBC51
socket GU5.3
max. per socket 12.0 W

ELECTRICAL

excl. driver
12 V
Class III

PHYSICAL

diameter 84 mm
height 76 mm
0.11 kg
wire springs

CUTOUT

diameter 76-79 mm
min. ceiling thickness 4 mm
max. ceiling thickness 27 mm
recessed depth 90 mm



**ELECTRICAL ACCESSORIES**

DRIVER TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
10W 12V 3-10VA phase-cut dim 220-240VAC		3-10VA	102-51-30	90221401
25W 12V 8-25VA phase-cut dim 220-240VAC		8-25VA	145-51-30	90221701