




PROJECT

TYPE

NOTES

QUANTITY

DATE



LUMINAIRE

Wall _____
 Surface _____
 Felt Limestone _____
 No matching RAL _____
 IP20 _____
 Interior _____
 365 lm _____

LED Module

2700 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 ≤ 3 SDCM (initial MacAdam) _____
 520 lm _____
 87 lm/W ^a _____

Optical

Indirect _____
 CIE flux code: 12 40 73 85 100 _____

Electrical

phase-cut dim _____
 220 - 240 V _____
 system 8.3 W _____
 Class I _____
 Standard _____


Physical

length 650 mm _____
 width 120 mm _____
 height 325 mm _____
 1.08 kg _____

datasheet.quicksum.material

Recycled PET Felt _____

^a Without electrical and optical losses



[‘336274LF3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.94	0.91	0.87	0.84
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.