



WEVER & DUCRÉ
LIGHTING

BOX mini 1.0 PAR16

258120M0 900199B1

ALGEMEEN

Plafond, Opbouw

Champagne

Zwart

IP20

Interieur

Output: 360^a, 430^b, 450^c lm

CIE flux code: 94 98 100 100 93

LED

Lamp PAR16

Stopcontact GU10

max. per socket 12.0 W

CRI ≥ 80 tot 90

ELEKTRISCH

100 - 240 V

LED inset 4.4^a tot 6.5^b W

Klasse 1

FYSISCH

Lengte 70 mm

Breedte 70 mm

Hoogte 82 mm

0.16 kg

^a PAR16 LAMP 2700K CRI80, binnenreflector zwart

^b PAR16 LAMP 2700K CRI90, binnenreflector zwart

^c PAR16 LAMP 3000K CRI90, binnenreflector zwart

Project

Type


Notities

Kwantiteit


Datum



Vierkanten downlight van gegoten aluminium, voor plafondopbouw; oppervlak Champagne; lampfitting GU10; lamptype PAR16; max. 12W; 100 - 240 V; beschermingsgraad IP20; PC1; UGR ≤ 19; inclusief enkele binnenreflector; lamp niet inbegrepen;



LICHTVERDELING



BOX

mini 1.0 PAR16

258120M0 900199B1

COMPONENTEN

Binnenreflector

| TYPE | ORDERCODE |
|---------------------|-----------------|
| BOX mini max. 10W | 9 0 0 1 9 9 B 1 |

ARMATUREN

PAR16 LED lamp

| TYPE | KLEUR | Ø · H (MM) | ORDERCODE |
|------------------------|--------|------------|-----------------|
| 2700K >90 CRI GU10 | Zwart | Ø50 · 60 | 9 0 1 2 2 8 B 3 |
| 3000K >90 CRI GU10 | Zwart | Ø50 · 60 | 9 0 1 2 2 8 B 5 |
| 2700K >90 CRI GU10 | Wit | Ø50 · 60 | 9 0 1 2 2 8 W 3 |
| 3000K >90 CRI GU10 | Wit | Ø50 · 60 | 9 0 1 2 2 8 W 5 |
| 2700K >80 CRI GU10 | Zilver | Ø50 · 60 | 9 0 5 2 2 7 S 2 |
| 3000K >80 CRI GU10 | Zilver | Ø50 · 60 | 9 0 5 2 2 7 S 4 |