



WEVER & DUCRÉ
LIGHTING

BOX mini 1.0 PAR16

258120M0 900199M1

ALGEMEEN

Plafond, Opbouw

Champagne

Champagne

IP20

Interieur

Output: 360^a, 430^b, 450^c lm

CIE flux code: 94 98 100 100 93

LED

Lamp PAR16

Stopcontact GU10

max. per socket 12.0 W

CRI ≥ 80 tot 90

ELEKTRISCH

100 - 240 V

LED inset 4.4^a tot 6.5^{b,c} W

Klasse 1

FYSISCH

Lengte 70 mm

Breedte 70 mm

Hoogte 82 mm

0.16 kg

^a PAR16 LAMP 2700K CRI80, binnenreflector champagne

^b PAR16 LAMP 2700K CRI90, binnenreflector champagne

^c PAR16 LAMP 3000K CRI90, binnenreflector champagne

Project

Type


Notities

Kwantiteit


Datum



Vierkanten downlight van gegoten aluminium, voor plafondopbouw; oppervlak Champagne; lampfitting GU10; lamptype PAR16; max. 12W; 100 - 240 V; beschermingsgraad IP20; PC1; UGR ≤ 19; inclusief enkele binnenreflector; lamp niet inbegrepen;



LICHTVERDELING



BOX

mini 1.0 PAR16

258120M0 900199M1

COMPONENTEN

Binnenreflector

TYPE	ORDERCODE
BOX mini max. 10W	9 0 0 1 9 9 M 1

ARMATUREN

PAR16 LED lamp

TYPE	KLEUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Zwart	Ø50 · 60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Zwart	Ø50 · 60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	Wit	Ø50 · 60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	Wit	Ø50 · 60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Zilver	Ø50 · 60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Zilver	Ø50 · 60	9 0 5 2 2 7 S 4